Fond du Lac Natural stone
BUILDING & LANDSCAPE STONE

Fond du Lac Dimensional w/Splitface

SPECIFICATIONS

GEOLOGY	Limestone
TYPE	60% Bedface, 40% Splitface
PATTERN	2:1 Sawn Course Heights | Dimensional Ashlar
HEIGHTS	2-1/4" (20%), 5" (40%), 7-3/4" (30%), 10-1/2" (10%): Full Bed & Thin Veneer
LENGTHS	8"-24" (Thin Veneer, crated/palletized material can exceed 20"); 8"-48" (Full Bed);
DEPTHS	3/4" - 1 1/4" (Thin Veneer); 3"-5" Full Veneer)
COLORS	Beige, Buff, Cream, Gray-Grey
COVERAGE	Full Bed Depth Veneer: 35-40 Square Feet Per Ton
WEIGHT	13.7 lbs. per square foot (Thin Veneer)
FLATS	10 s/f Box; 100 s/f Crate, 180 s/f Crate; 100 s/f pallet, 180 s/f pallet
CORNERS	10 l/f Box; 100 l/f Crate; 100 l/f pallet, Crated material can exceed 20"
NOTES	Pre-packaged 60% Fond du Lac Dimensional, 40% Fond du Lac Clean-Split

ASTM C-97

Water Absorption %	.31 psi
Bulk Specific Gravity	2.83 psi

ASTM C-170

Parallel to Rift, Dry	36100 psi
Parallel to Rift, Wet	32000 psi
Perpendicular to Rift, Dry	35800 psi
Perpendicular to Rift, Wet	30000 psi

ASTM C-99

Parallel to Rift, Dry	3770 psi
Parallel to Rift, Wet	3500 psi

ASTM C-880

Perpendicular to Rift, Dry	1780 psi
Perpendicular to Rift, Wet	1730 psi

CERTIFIED GENUINE STONE
GOLD QUARRIER
ANSI/NSC 373-2013
C0290908-101

CERTIFIED GENUINE STONE
GOLD FABRICATOR
ANSI/NSC 373-2013
C0289215-101

Fond du Lac Natural Stone | fdlnaturalstone.com
N4224 Hwy 175 PO Box 347 Fond du Lac, WI 54936-0347
Phone: 920-923-2800 | Toll Free: 877-923-2800 | Fax: 920-923-3800